

ADITIVO 51

Anti-graffiti Additive



DESCRIPTION



Additive for 2K coatings (**URKINATO**, **ALFAPUR 3748**, **URKIVOC** and **BESAGLASS**, etc.). It reduces the adherence of dirt and improves the capacity to remove graffitis from them, in addition to increasing its sliding power.

SURFACE PREPARATION



When repainting surfaces with coats containing **ADITIVO 51**, make sure the surface is well prepared to prevent the lack of adhesion.

USE



Replace the dilution thinner indicated in the converter's Technical Data Sheet with **ADITIVO 51** and apply each product as indicated.

Note on recoatability: It will differ from the Technical Data Sheet of each product.

DRY FILM CHARACTERISTICS

To remove graffiti, pressure wash with soap and water or degrease with **SD-7 10**. Recoatability: After previously sanding, degrease and drying.

SAFETY INSTRUCTIONS

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

STORAGE

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

VOC

The VOC content of ADITIVO **51** is a maximum of 900 g/l.

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**
