TECHNICAL DATA SHEET

BERNARDO ECENARRO, S.A.
Ugarte Industrialdea, 147
20720 Azkoitia (SPAIN)
Tel.: +34 +34 943 74 28 00
Fax: +34 +34 943 74 06 03
www.besa.es

UV-799

UV PROTECTION ADDITIVE

Edition: 020

Cod: 7079900000.00000.020

APPLICATION

UV protection additive for 2K polyurethane or acrylic products. Prevents degradation caused by ultraviolet light in the finishing film, resulting in excellent gloss retention (up to 30%) and long-term color stability. Used in PUR products such as BESA-GLASS, URKI-NATO, BESA-NATO, URKI-VOC, etc. Mainly intended for painting for painting parts exposed to outdoor conditions.

UV-799 PROTECTION ADDITIVE is a VOC-free product.

APPICATION INSTRUCTIONS

Add between 2.5% and 5% to component A, then mix thoroughly until fully incorporated. Mechanical stirring is recommended. Exceeding 5% does not provide additional resistance benefits.

The addition of the additive does not affect the appearance of enamels. In satin and matt finishes, gloss may increase slightly by approximately 5-10%.

FEATURES OF DRY FILM

Product type	UV light protection

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25ºC recommended. Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.

BERNARDO ECENARRO,S.A. is free for making any modification, in any moment, of the characteristics of the product. In this case, a new Technical Data Sheet will be edited. Responsabilities will not be accepted if they are due to the non observation of the conditions marked.