



Bernardo Ecenarro S.A.

TECHNICAL DATA SHEET

BERNARDO ECENARRO, S.A.

Ugarte Industrialdea, 147

20720 Azkoitia (SPAIN)

Tel.: +34 +34 943 74 28 00

Fax: +34 +34 943 74 06 03

www.besa.es

Page 1 from 1

UV-799

UV PROTECTION ADDITIVE

Edition: 020 2025/02

Cod: 7079900000.00000.020

APPLICATION

UV protection additive for 2K polyurethane or acrylic products. Prevents degradation caused by ultraviolet light in the finishing film, resulting in excellent gloss retention (up to 30%) and long-term color stability. Used in PUR products such as BESA-GLASS, URKI-NATO, BESA-NATO, URKI-VOC, etc. Mainly intended for painting parts exposed to outdoor conditions.

UV-799 PROTECTION ADDITIVE is a VOC-free product.

APPLICATION INSTRUCTIONS

Add between 2.5% and 5% to component A, then mix thoroughly until fully incorporated. Mechanical stirring is recommended. Exceeding 5% does not provide additional resistance benefits.

The addition of the additive does not affect the appearance of enamels. In satin and matt finishes, gloss may increase slightly by approximately 5-10%.

FEATURES OF DRY FILM

Product type	UV light protection
--------------	---------------------

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended.

Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.