

C 45



PVC TILTS SYSTEM



PRODUCT

URKI-LON FLEXIBLE ENAMEL FOR CANVAS

FIELD OF APPLICATION

Paint System developed for painting and labelling of canvas and PVC Tilts. Outstands for its quick drying, flexibility and adhesion on this surface.

PHYSICAL PROPERTIES

	Urki-Lon
Type of product	Acrylic
Density 20° C	0,96 - 1,12
Supply viscosity at 20° C	115-135 sec. Ford n° 4
Solid Content (% weight)	40 - 50%
Solid Content (% volume)	32 - 35%
V.O.C.	696 g/l (ready to use)
Color	s/m URKI-SYSTEM



SURFACE PREPARATION: PVC TILTS

The surface must be degreased with Thinner Nr 94. Very important to check the surface is PVC and do not exceed the recommended dry film thickness in order to avoid longer drying time and cracking caused by the thick layer.

Very good adhesion on other surfaces such as PMMA, PVC, PVG foam previously degreased.

C 45

PVC TILTS SYSTEM

APPLICATION URKI-LON



FEATURES OF DRY FILM

	Urki-Lon
Theoretical yield	13 - 14 m ² / l. (25 my)
Gloss 60 - 60°	55 - 65%
Recoatibility	1 h.

RESISTANCE



FLEXIBILITY