


URKIPROTEC

Repaintable Anti-stone Chip



DESCRIPTION

URKIPROTEC Anti-stone chip with a satin aspect and rubber nature, provides a hard, strong and long-lasting coat. Designed to reproduce the original finish and offer protection against grit, salt, moisture and oxidation and even to absorb engine noise and vibration.

It is recoatable by most paint systems.

COLORS

URKIPROTEC	9005	7470	9110
------------	------	------	------

SURFACE PREPARATION

Surfaces must be clean, dry and exempt of dust, grease and rust. For better adhesion of the product, peeling parts, dirt and rust must be removed.

USE

Apply 1 cross coat to achieve up to 300 microns.

APPLICATION

Anti-stone chip gun Application pressure	3-6 bar
Number of coats Total thickness	1 cross coat 300 µm
Drying Time 20°C 60°C	60' 30'

SAFETY INSTRUCTIONS 

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

STORAGE 

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

VOC 

The VOC content of URKI**PROTEC** is a maximum of 840 g/l in compliance with European regulation 2004/42/EC IIB(E) (840) <840 g/l.

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**
