

**0100**  
DEFOAMER 100

Edition: 020 2012/09  
Cod: 9000000100.00000.020

### APPLICATION

#### "USE ONLY IN INDUSTRIAL FACILITIES"

Additive used to improve the application or epoxy nature products, as URKI-POX, mainly in brush applications and with a quick result in defoaming and levelling.

0100 Defoamer additive has also antisilicon properties and improves the scratch resistance of the paint.

### PHYSICAL PROPERTIES

|                          |                           |
|--------------------------|---------------------------|
| Density at 20°C (g/cc)   | 0,88 ± 0,02               |
| V.O.C. (g/l)             | 400                       |
| Flash Point              | 0-21°C Method: closed cup |
| Punto de ebullición (°C) | > 35°C                    |
| Type of product          | Defoamer additive         |
| Colour                   | Clear and colourless      |

### APPLICATION INSTRUCTIONS

Add maximum 2% of the total paint.

Not recommended as a preventive measure. Adding more than the advised % may make the problem even worse or cause loss of adhesion between coats when recoated.

### FEATURES OF DRY FILM

|   |                 |
|---|-----------------|
| - | Defoamer effect |
|---|-----------------|

### COMPOSITION

|                 |                                |
|-----------------|--------------------------------|
| Type of product | Cetonic / Polydimethylsiloxane |
|-----------------|--------------------------------|

### STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended.

Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.