

ANTIFOGGANT

TECHNICAL DATA SHEET

BERNARDO ECENARRO, S.A.

Ugarte Industrialdea, 147 20720 Azkoitia (SPAIN) Tel.: +34 +34 943 74 28 00 Fax: +34 +34 943 74 06 03 www.besa.es

Page 1 from 1

DELAYING THINNER

Edition: 020 2012/09 Cod: 900000001.00000.020

APPLICATION

"USE ONLY IN INDUSTRIAL FACILITIES"

Slow evaporating thinner used to avoid blooming specially in nitro-synthetic products. Advised in atmospheres of high humidity or temperature.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	0,900 ± 0,02
V.O.C. (g/l)	900
Flash Point	21-55°C Method: closed cup
Boiling point (°C)	> 35°C
Type of product	Thinner
Colour	Clear and colourless

FEATURES OF DRY FILM

	-	Antifoggant effect
ОМР	OSITION	

COMPOSITION

|--|

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended. Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.