

## E-750

### Accelerator for Acrylics-Polyurethanes



#### DESCRIPTION

Additive formulated to reduce drying time in 2K polyurethane or acrylic products without losing its properties.

It allows a reduction in painting time, as it can be taped more quickly for processes where the application of several colours is required.

It should not be used on epoxy products.

#### USE

Add between 1 and 3% to the total amount of paint.

It is not recommended to use it as a preventive measure. Exceeding the indicated percentages can produce a considerable shortening of the pot life and cause a loss of gloss, to worse extensibility, boiling, etc.

The additive can be added to either Component A or mixture A + B mixture. It is not advisable to add it to the hardener, as it could suffer from stability problems.

#### DRY FILM CHARACTERISTICS

Functionality	Accelerating effect
---------------	---------------------

---

**SAFETY INSTRUCTIONS** 

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

---

**STORAGE** 

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

---

**VOC** 

The VOC content of **E-750** is a maximum of 863 g/l.

---

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**

---