

URKISEAL 4020
PRIMER FOR GLASS AND METAL PLATE
(WINDSCREEN)

APPLICATION

URKISEAL 4020 is a black primer which changes into an opaque and hard film once dry. Improves the adhesion on Polyurethane Sealants. Can be used on glass, aluminium, cement, wood and plastics. Also can be used as barrier between sealant and paint for avoid the migration of plasticizers.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	0,92 ± 0,03
Aspect	Low viscosity liquid
%Solids content (weight / volume)	29,5 % ± 1,5 % weight
V.O.C. (g/l)	<780 (Ready to use) - (2004/42/CE) IIB (C) (780)
Type of product	Prepolymer Polyurethane
Colour	Black 9005

SURFACE PREPARATION

The surfaces must be clean, dry and free from grease and dust. The cleaning can be done with URKISOL 88 depending on the substrate to paint.

(Verify the compability of the thinner used on the substrates).

APPLICATION INSTRUCTIONS

(Between 5°C and 40°C)

Shake the can vigorously before using.

Apply using a brush or wired felt in a continuous flowing movement.

Reacts and dries with the humidity of the air after the evaporation of the solvents.

The bottles must be closed after use.



10-15' air drying

FEATURES OF DRY FILM

Recoatibility: After dry, apply URKISEAL 4000 in time of 1 hour.

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended.

Can life: **12 months** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.

Do not open bottle until use and do not use after 24 h. opened.