

**URKI-BOOTH
BOOTH PROTECTION (WALL)**Edition: 020 2012/05
Cod: 0303010020.00000.020**APPLICATION**

This product has been specially developed for protecting the walls of spray booths. The dust and dirt will adhere on the product, avoiding suspended particles to stick on the painted surface.
The product is transparent, so it does not reduce the lighting nor affect the colour matching.
URKI-BOOTH does not contain silicones and it is completely biodegradable.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	0,970 ± 0,005
V.O.C. (g/l)	4
Type of product	Water based solution
Colour	Transparent

SURFACE PREPARATION

Clean the surface where URKI-BOOTH will be applied.

APPLICATION INSTRUCTIONS

It can be easily applied by spray gun, brush or roller, directly from the can.
It can be removed with hot water or high-pressure water.

FEATURES OF DRY FILM

-	Adhesive features for dust
---	----------------------------

Theoretical yield (m ² /l)	Approx. 8 L per Booth (Standard)
Gloss 60°-60°	-
Second layer	-

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended.
Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.