

# **TECHNICAL DATA SHEET**

BERNARDO ECENARRO, S.A.

Ugarte Industrialdea, 147 20720 Azkoitia (SPAIN) Tel.: +34 +34 943 74 28 00 Fax: +34 +34 943 74 06 03

www.besa.es

Page 1 from 1

Edition: 020 2016/06 Cod: 2000402250.00000.020

#### VA 2250

WATERBASED TINTING PASTE

## APPLICATION

Transparent pigment concentrates for waterborne clear coats: VA 7400, VA 7405

# PHYSICAL PROPERTIES

%Solids content (weigth / volume)	20-75% weight
Colour	Blue 50

### **APPLICATION INSTRUCTIONS**

Mix well before use.

Mix the Adhesion promoter VA8450 slowly with a low speed stirrer with the clear coat.

Add 0-20 parts of the pigment concentrate to the clear coat.

Add the pigment concentrates one by one with a low speed stirrer. Adjust viscosity application with demineralized water Mix carefully and filter 125 microns.



VA 8450 100:2 weight



PASTE 100/0-20

## STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended. Can life: 1 year from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.