

TECHNICAL DATA SHEET

 BERNARDO ECENARRO, S.A.

 Ugarte Industrialdea, 147

 20720
 Azkoitia (SPAIN)

 Tel.: +34 +34 943 74 28 00

 Fax: +34 +34 943 74 06 03

 www.besa.es

Page 1 from 1

VA 2290

WATERBASED TINTING PASTE

Edition: 020 2016/06 Cod: 2000402290.00000.020

APPLICATION

Pigment concentrate for waterborne clear coats: VA 7400, VA 7405

PHYSICAL PROPERTIES

%Solids content (weigth / volume)	20-75% weight
Colour	Black 90

APPLICATION INSTRUCTIONS

Mix well before use.

Mix the Adhesion promoter VA8450 slowly with a low speed stirrer with the clear coat.

Add 0-20 parts of the pigment concentrate to the clear coat.

Add the pigment concentrates one by one with a low speed stirrer. Adjust viscosity application with demineralized water

Mix carefully and filter 125 microns.





PASTE 100/0-20

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended. Can life: **1 year** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.