

TECHNICAL DATA SHEET

BERNARDO ECENARRO, S.A.

Ugarte Industrialdea, 147
20720 Azkoitia (SPAIN)
Tel.: +34 +34 943 74 28 00
Fax: +34 +34 943 74 06 03

www.besa.es

Page 1 from 1

Edition: 020 2016/06 Cod: 2000402442.00000.020

VA 2442

COLORANT SOLUTION

APPLICATION

"USE ONLY IN INDUSTRIAL FACILITIES"

High concentrated dye to make transparent colors with waterborne clear coats: VA 7400, VA 7405

PHYSICAL PROPERTIES

%Solids content (weigth / volume)	9-16% weight
Colour	Pink Fluo 42

APPLICATION INSTRUCTIONS

Mix well before use.

Mix the Adhesion promoter VA8450 slowly with a low speed stirrer with the clear coat.

Add 0-20 parts of the dye to the clear coat.

Add the dyes one by one with a low speed stirrer. Adjust viscosity application with demineralized water Mix carefully and filter 125 microns.



VA 8450 100:2 weight



CLEARCOAT COLORANT 100/0-20

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended. Can life: **1 year** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired