

F-862

QUICK DRYING PRIMER FOR STEEL

URKI-SYSTEM

CONVERTER: 6095 / CONV F-862

RELATION PASTE / CONV.: 15/85

Edition: 021 2014/01

Cod: 3909500000.00000.021

APPLICATION

"USE ONLY IN INDUSTRIAL FACILITIES"

Economical primer for the protection of Metallic Structures, Boilermaking, Metallic Carpentry, Blacksmiths, Forge, etc....

It may also be used as a Matt paint for iron and wood, for making marks.

Specially recommended in fast process where a quick drying is recommended. Outstands for its good adhesion and overall properties.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	1,35 - 1,50
Grinding Fineness (μ)	40 - 50
Supply viscosity at 20°C	90 - 110 KU (Stormer)
%Solids content (weight / volume)	71 % ± 2 weight; 53 % ± 2 volume.
V.O.C. (g/l)	495 (Ready to use) Airless Application
Type of product	Modified Alkyd
Colour	URKI-SYSTEM

SURFACE PREPARATION

-Iron and Steel: Degrease and deoxidize previously

-Wood: Brush and remove dust.

Recoatable with : URKI-RAPID, URKI-CLOR, URKI-FLEX, BESA-FER, BESA-LUX y URKI-SAL .

APPLICATION INSTRUCTIONS

Dipping: Dilute at 30-35 sec.

Ford nº 4 with URKISOL-170



20-25"
FORD nº 4



URKISOL 222
5-10 %



URKISOL 88
30-35 %



30-40 my



Touch free 10'
Tack free 45'



5-10'



URKISOL 88
5-10 %

FEATURES OF DRY FILM

Theoretical yield (m ² /l)	14 - 15 (35 my)
Gloss 60°-60°	Matt < 2 %
Second layer	1 h. ó 24 h.

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended.

Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.