

URKI-TRAF
LINE MARKING PAINT

APPLICATION

"USE ONLY IN INDUSTRIAL FACILITIES"

Synthetic paint, with excellent covering and rapid-drying qualities.

This product has been developed for floor marking purposes in garages, industrial way networks, sports centres, etc.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	1,60 ± 0,05
Grinding Fineness (µ)	40 - 50
Supply viscosity at 20°C	90 - 100 KU (Stormer)
%Solids content (weight / volume)	72 % ± 2 weight; 50 % ± 2 volume.
V.O.C. (g/l)	496 (Ready to use)
Type of product	Synthetic Resin
Colour	Yellow 1442, White 9110

SURFACE PREPARATION

Remove any dust and grease from the surface to be painted. Use Thinner nº. 10 for Cleaning.

APPLICATION INSTRUCTIONS

Preferably apply with Airless.

Dilution with 5-10 % URKISOL-170



50-70"
FORD nº 4



URKISOL 222
5 %



URKISOL 170



Supply
Viscosity



40-60 my



Touch free 5'
Tack free 15'

FEATURES OF DRY FILM

Theoretical yield (m ² /l)	10 - 12 (45 my)
Gloss 60°-60°	Matt <5%
Second layer	2 to 3 h.

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended.

Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.