

### SPRAY F-4101 N

HEAT RESISTANT PAINT BLACK 450°C

Edition: 020 2017/12

Cod: 6060409005097.00000.020

#### APPLICATION

Heat resistant Paint up to continuous 400-450°C, with excellent mechanical properties, adhesion and rust resistance. Suitable for protection the protection of pieces subject to high temperatures, such as exhausts, ovens, chimney, ...

#### SURFACE PREPARATION

The surfaces to be painted should be rust and dirt free, thoroughly degreased.

#### APPLICATION INSTRUCTIONS

Shake the can during 2-3 minutes before using Spray F-4101 N  
Apply in 2-3 layers, leaving 5-10 min. in between layers.  
Having used the spray, turn it upside down and press in order to clear the nozzle.

Note. Do not exceed the advised thickness.



Painting range  
20-30 cm



15-20 my



5-10 min.



Touch free 15´  
Tack free 30´  
100°C/15min

#### FEATURES OF DRY FILM

Colour	Black
Gloss 60°-60°	Matt-Satin 10-15%
Second layer	1 h.

#### STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended.  
CAUTION: Do not expose the can to temperatures over 50°C.  
Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.