

**BESA-LUX SAT**  
SATIN-FINISHED SYNTHETIC ENAMEL

URKI-SYSTEM

CONVERTER: 6052 / CONV B-LUX SAT

RELATION PASTE / CONV.: 35/65

Edition: 020 2011/11

Cod: 6905200000.00000.020

### APPLICATION

#### "USE ONLY IN INDUSTRIAL FACILITIES"

Protection and decoration of wooden and metal surfaces such as furniture, doors and windows, gates, etc.

Outstands for its easy application by brush and levelling with a pleasant gloss, and satin finish and therefore suitable for interior decoration.

### PHYSICAL PROPERTIES

Density at 20°C (g/cc)	1,00 - 1,27
Grinding Fineness (μ)	20 - 30
Supply viscosity at 20°C	80 - 85 KU (Stormer)
%Solids content (weight / volume)	60 - 69 % weight; 51 - 55 % volume.
V.O.C. (g/l)	398 (Ready to use) Brush application
Type of product	Modified Alkyd
Colour	URKI-SYSTEM

### SURFACE PREPARATION

-Steel: Thoroughly degreased and deoxidized. Prime with F-29 or F-809 Anti-Rust Zinc Phospahte Primer.

-Wood: Prime with Synthetic Sealers and sand before applying the topcoat.

### APPLICATION INSTRUCTIONS



20-25"  
FORD nº 4



URKISOL 222



URKISOL 170  
25-30 %



30-40 my



Touch Free 1 h.  
Tack Free 8 h.

### FEATURES OF DRY FILM

Theoretical yield (m <sup>2</sup> /l)	13 - 15 (35 my)
Gloss 60°-60°	20 - 30 %
Second layer	24 h.

### STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended.

Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.