

VD 7051
PUR SOFT MATT CLEARCOAT

Edition: 020 2016/06
Cod: 7005100000.00000.020

APPLICATION

"USE ONLY IN INDUSTRIAL FACILITIES"

Soft touch two-component clear coat. Conventional spraying.
Good mechanical properties, scratch resistance and elasticity.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	1,00 ± 0,02
Supply viscosity at 20°C	35 - 40 sec Ford n ^o 4
%Solids content (weigh / volume)	47 % ± 2 weight
Type of product	Polyurethane
Colour	Transparent matt

SURFACE PREPARATION

On glass substrates it must be applied first a flash primer like VD 3100 or VD 3105.
The surface should be dry and free from dust, dirt, grease and oil.

APPLICATION INSTRUCTIONS

Conventional spraying.



VD8287
100:10 weight



1 h.
It is recommended to use a two component spraying system



28-33"
FORD n^o4



VD 9041
5-10%



20-50 my



1-3'
20-25°C



15' / 150°C
10' / 180°C
Glass



1H/ 60-80°C
Plastic

FEATURES OF DRY FILM

Gloss 60°-60°	10 % ±0.5 (flat glass)
---------------	------------------------

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended.
Can life: **1 year** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.