

F-3131 STRIPPING LACQUER

APPLICATION

"USE ONLY IN INDUSTRIAL FACILITIES"

Stripping Lacquer for temporary protection, providing the product a good anti-rust qualities for not excessively long periods of time and easy to peel off in one single strip.

Very useful in Aluminium Carpentry, protection of Steel parts during storage and transport, protection of mechanized areas in the Machine Tool sector, etc.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	0,91 ± 0,02
Grinding Fineness (μ)	5 - 10
Supply viscosity at 20°C	120" ± 10 Ford nº 4
%Solids content (weigh / volume)	30% ± 2 weight; 21 % ± 2 volume.
V.O.C. (g/l)	645
Type of product	Vinyl
Colour	Blue 5122

SURFACE PREPARATION

Direct application on the metallic surface, Steel or Aluminium thoroughly degreased.

Avoid the application of this product on surfaces subject to temperatures of above 70-80°C or on surfaces painted with products of a low reticulation.

APPLICATION INSTRUCTIONS

Application by brush recommend in order to achieve a thickner film and therefore easier to strip off.



15-18"
FORD nº 4



Supply
Viscosity



Thinner
URKISOL 300
90-100 %



20-40 my



Tack Free 60'

FEATURES OF DRY FILM

Theoretical yield (m ² /l)	7 - 8 (30 my)
Gloss 60°-60°	Satin
Second layer	

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended.

Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.