

SPRAY URKI-BLEND

BLENDING THINNER

Edition: 020 2017/12

Cod: 9000000852097.00000.020

APPLICATION

The Urki-Blend Spray presents a mixture of solvents destined to help to the integration of new and old paint in body partial repair and touching-up. The VOC content is less than 840 g / l (2004/42/CE) IIB (E)

SURFACE PREPARATION

Integrator used in touching-up and spot repair. Sand the old paint on the peripheral area of the patch with P2000-4000.

APPLICATION INSTRUCTIONS

Shake the can. Apply in 2-3 light layers without waiting for evaporation between them. Apply in the limits of the repaired area (patch) immediately after the last finishing coat (clearcoat or single coat) to facilitate the integration of the new paint with the old and this way make easier the subsequent polishing process.

After use, turn upside down the can and clean the valve



Painting range
20-30 cm



2-3 thin layers
without evaporation
between them

FEATURES OF DRY FILM

Colour	Colorless
--------	-----------

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended. CAUTION: Do not expose the can to temperatures over 50°C.

Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.