


## 2K URKISPRAY

2K Polyurethane Refillable Charge



### DESCRIPTION



2K spray for professional use. Formulated with propellant gases, solvents and specific additives which, combined with its nozzle, provide a high quality finish.

Specially designed for 2K acrylic or polyurethane paints.

### USE



- Remove the cap from the can and insert the filling cup into the valve.
- Fill the cup up to the packaging mark.
- Introduce the spray into the aerosol filling machine following the instructions.
- Once filled with the desired paint, wait one minute and then shake it well.
- Spray some of the product until the dispersion of it is uniform.



### RECOMMENDED FILLING PRODUCTS



URK**VOC**, URK**INATO**, BESAG**LASS**, BESAN**ATO**, BESAN**ATO SAT**.

See the characteristics of each product in its corresponding Technical Data Sheet.

---

**SAFETY INSTRUCTIONS** 

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

---

**STORAGE** 

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

CAUTION: Under no circumstances should the packaging exceed 50°C.

---

**VOC** 

The VOC content of 2K URKISPRAY and indicated qualities is a maximum of 840 g/l in compliance with the European regulation 2004/42/CE IIB(E) (840) <840 g/l.

---

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**

---