


## URKICUT Cutting Compound



### DESCRIPTION

Effective and high quality product designed for clearcoat polishing in the refining sector. Its formulation removes quickly and effectively surface defects, spray and sanding grain marks P1000-P1500. It has a high level of polish, providing a shiny surface, without fogging or marks.

Its balanced composition in solid and liquid ingredients minimises the generation of dust, reducing contamination of the workplace. The remains are easy to clean up. A subsequent shining process with URKI**GLOSS** is recommended.

High abrasion power with a medium polish process. It is versatile, valid for both recently repaired and aged coatings.

Contains no silicones.

### COLORS

URKICUT

WHITE

### USE

It is important to apply appropriate and sufficient pressure on the polisher in the first coats on the surface to remove any marks or surface defects.

	Cleaning	Clean and moisten
	Sanding	P1000 - P1500
	Polishing	1200 - 2000 RPM
	Cleaning	Clean with a microfibre cloth

**SAFETY INSTRUCTIONS** 

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

---

**STORAGE** 

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

---

**VOC** 

The VOC content of URKICUT is a maximum of 200 g/l in compliance with European regulation 2004/42/EC IIB(A) (200) <200 g/l.

---

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**

---